

G2 Spoke Classroom Audio System™ – Speakers



Product Name

- Designed for today's multimedia classroom
- Dual-cone speaker with 10 oz magnet (ceiling models)
- Optimized for speech and digital content
- Ceiling, wall, and cut-in versions
- Fast, simple installation
- UL listed for plenum use
- Standard 8 Ohm connection

The G2 Spoke Classroom Audio System

The G2 Spoke Classroom Audio System is an extraordinary blend of technology, features, ease-of-use, and convenience. Systems from as few as two to as many as eight speakers. Assistive listening transmitter included as standard! Up to four microphones. Spoke is available in stand-alone configurations for classrooms with existing display technology or embedded in G2's newest line of Interactive Flat Panel Displays named G2 *slim*.

It's All About the Speakers

G2 Spoke has great electronics, astonishing electronics including standard Assistive Listening transmitter and 4 wireless microphone receivers. But in the end, the speakers make the biggest difference. That's why we put so much effort and engineering into our four speaker models.

Designed for Schools




Schools are tough environments. They present a wide range of temperature and humidity levels. It is not unusual for classrooms to reach over 100 degrees while the students are on summer vacation. Humidity in some regions can be over 70% most of the year. Speakers need to be commercial grade devices designed to last year, after year, after year.

Flexibility

Districts, and even individual schools, have varying needs from classroom-to-classroom and building-to-building. The speakers that have been designed to complement G2 Spoke can accommodate a breadth of requirements.

There are two sizes of drop-in ceiling tile speakers for extremely fast installation. Plus cut-in speakers to trade off additional installation time for reduced capital cost. And for those classrooms without a drop-down ceiling, G2 offers a wall-mounted system. Of course, the four models can be mixed and matched within a room, building, or district.

Specifications

Specification/Model	1' x 2' Ceiling Tile Speaker	2' x 2' Ceiling Tile Speaker	Cut-In Speaker	Wall-Mount Speaker
				
Impedance	8 Ohm			
Driver size	8" Dual Cone			4" woofer + 3/4" dome tweeter
UL listed for plenums	Yes			Not Applicable
Average sensitivity	92 dB SPL, 1W/1M			
Power rating	20W RMS EIA 426A Standard			20W RMS
Maximum output	20 W @ 8 Ohms			
Calculated output	102 dB-SPL 12W/1M			
Frequency response	65 Hz - 17 kHz EIA 426A Standard			80Hz - 20kHz
Typical coverage angle	100° Included Angle -6 dB / 2 kHz, Half space			
Audio connection	6" leads pre-stripped			Binding Screw
Unit weight	3.85 lbs	4.05 lbs	?	?
Unit dimensions	1' x 2'	2' x 2'	?	?
Shipping weight	?	?	?	?
Shipping dimensions	?	?	?	?
Included	<ul style="list-style-type: none"> • Speaker • T-bar bracket • 50' plenum-rated cable 	<ul style="list-style-type: none"> • Speaker • 50' plenum-rated cable 	<ul style="list-style-type: none"> • Speaker • Grille – white • 50' plenum-rated cable 	<ul style="list-style-type: none"> • Speaker • Wall mount • 50' plenum-rated cable

More Information

Additional details, pricing and availability are available from your authorized G2 reseller at www.G2SystemsInc.com/WhereToBuy.



All specifications are subject to change without notice.